

# THOR



## PLASMA 12-STRAND WITH SPECTRA COVER

PART #	SIZE/DIAMETER		CORE DIAMETER		STANDARD LENGTH (FT.)	WT./COIL (LBS.)	TENSILE STRENGTH (LBS.)
	(IN)	(MM)	(IN)	(MM)			
THOR58	5/8	16	1/2	12	600	60	35,100
THOR34	3/4	19	5/8	16	600	98	58,000
THOR78	7/8	22	3/4	19	600	122	70,900
THOR1	1	24	13/16	21	600	147	75,600
THOR118	1 1/8	28	7/8	22	600	199	95,000
THOR114	1 1/4	32	1	24	600	216	113,000
THOR112	1 1/2	36	1 1/4	32	600	334	183,400
THOR158	1 5/8	40	1 5/16	34	600	385	201,000
THOR134	1 3/4	44	1 1/2	36	600	477	228,800
THOR2	2	48	1 5/8	40	600	533	242,400

\* LISTED TENSILE STRENGTHS REPRESENT MINIMUM TENSILE FOR SPLICED ROPES.

\* USES - WINCH LINES, GILSON LINES, FRAMELINES & TOWLINES

**DANTRAWL**  
INCORPORATED

MODERN GEAR FOR TODAY'S PROFESSIONAL FISHERMAN