

Nylon



Double Braid *

ITEM #	DIAMETER (IN)	FT./COIL	WT./COIL (LBS)	MIN. TENSILE STRENGTH (LBS)
NRPSS14	1/4	600	12	1,900
NRPSS516	5/16	600	17	2,900
NRPSS38	3/8	600	23	4,200
NRPSS12	1/2	600	40	7,400
NRPSS58	5/8	600	72	14,800
NRPSS34	3/4	600	90	19,000
NRPSS78	7/8	600	132	28,300
NRPSS1	1	600	156	33,500
NRPSS118	1 1/8	600	216	44,900
NRPSS114	1 1/4	600	246	52,300
NRPSS112	1 1/2	600	360	74,000
NRPSS158	1 5/8	600	444	92,400
NRPSS134	1 3/4	600	534	110,900
NRPSS2	2	600	636	131,500
NRPSS218	2 1/8	600	744	152,800
NRPSS214	2 1/4	600	864	181,000
NRPSS212	2 1/2	600	990	201,000
NRPSS258	2 5/8	600	1,128	222,000
NRPSS234	2 3/4	600	1,272	248,000
NRPSS3	3	600	1,428	277,000

* Available in other lengths.

Uses: riblines, midwater trawls, zipperlines, mooring lines, anchor lines, general purposes.

Elongation at break, 30%-35%.

DANTRAWL
INCORPORATED

MODERN GEAR FOR TODAY'S PROFESSIONAL FISHERMAN

B-17