

# Spectra™

## 12-Strand Single Braid \*

### High Strength



TENSILE STRENGTH ITEM #	DIAMETER (IN)	FT./COIL	WT. (LBS)	(LBS)
SPEC1218	1/8	600	3	1,800
SPEC12316	3/16	600	6	3,600
SPEC1214	1/4	600	10	6,000
SPEC12516	5/16	600	16	9,000
SPEC1238	3/8	600	22	13,900
SPEC12716	7/16	600	26	14,800
SPEC1212	1/2	600	38	22,500
SPEC12916	9/16	600	47	27,700
SPEC1258	5/8	600	64	36,600
SPEC1234	3/4	600	80	43,200
SPEC1278	7/8	600	118	61,000
SPEC121	1	600	141	72,000
SPEC12118	1 1/8	600	192	91,800
SPEC12114	1 1/4	600	218	102,600
SPEC12112	1 1/2	600	311	141,300
SPEC12158	1 5/8	600	395	167,000
SPEC12134	1 3/4	600	470	198,000
SPEC122	2	600	549	225,000
SPEC12218	2 1/8	600	654	270,000
SPEC12214	2 1/4	600	732	317,700
SPEC12212	2 1/2	600	888	360,000
SPEC12234	2 3/4	600	1,122	405,000
SPEC123	3	600	1,284	508,500

\* Available in other lengths. Uses: riblines, lifting straps, codend winches, general purposes.

**DANTRAWL**  
INCORPORATED

**MODERN GEAR FOR TODAY'S PROFESSIONAL FISHERMAN**

**B-14**

4776 Shilshole Ave. N.W. • Seattle, WA 98107 • Phone: 206-789-8840 • Fax: 206-789-8973 • sales@dantrawl.com