

BRIDON AMERICAN

Wire

Bridon Dyform™
6x19 Classification
IWRC



ITEM #	SIZE (IN)	SIZE (MM)	MIN B/LOAD (US TONS)	WT./FT. (LBS)
BD916IWRC	9/16	14.0	15.0	0.59
BD58IWRC	5/8	16.0	19.5	0.77
		18.0	24.7	0.98
BD34IWRC	3/4	19.0	27.4	1.09
		20.0	30.5	1.21
BD78IWRC	7/8	22.0	37.9	1.46
		24.0	43.5	1.74
BD1IWRC	1	25.4	51.3	2.06
		28.0	61.7	2.38
BD118IWRC	1 1/8	28.6	62.6	2.46
		30.0	68.6	2.73
BD114IWRC	1 1/4	31.8	74.0	3.09
BD138IWRC	1 3/8	34.9	93.0	3.70
BD112IWRC	1 1/2	38.1	113.4	4.43

* Minimum Break Load and weight per foot are based upon manufacturers specifications.

** Refer to manufacturer's literature for detailed information and warnings, inspection criteria.

DANTRAWL

INCORPORATED

MODERN GEAR FOR TODAY'S PROFESSIONAL FISHERMAN

H-5

4776 Shilshole Ave. N.W. • Seattle, WA 98107 • Phone: 206-789-8840 • Fax: 206-789-8973 • sales@dantrawl.com